

## Motores trifásicos con brida C

Dimensiones de motores con brida C en pulgadas

Armazón	R	AA	BD	AJ	AK	U	AH	BA	ES	S	BF # cantidad	BF diam. roscado
143/145TC	0.771	0.75	6.5	5.875	4.5	0.875	2.125	2.25*	1.41	0.188	4	16 NC 3/8"
182/184TC	0.986	0.75	9	7.250	8.5	1.125	2.625	2.75*	1.78	0.25	4	13 NC 1/2"
182/184TCH	0.986	0.75	6.5	5.875	4.5	1.125	2.625	2.75*	1.78	0.25	4	16 NC 3/8"
213/215TC	1.201	1.00	9	7.250	8.5	1.375	3.125	3.5*	2.41	0.312	4	13 NC 1/2"
254/256TC	1.416	1.25	10	7.250	8.5	1.625	3.750	4.25*	2.91	0.375	4	13 NC 1/2"
284/6TC	1.591	1.50	10.75	9	10.5	1.875	4.38	4.75	3.28	0.5	4	13 NC 1/2"
284/6TSC	1.416	1.50	10.75	9	10.5	1.625	3	4.75	1.91	0.38	4	13 NC 1/2"
324/6TC	1.845	2.00	12.75	11	12.5	2.125	5	5.25	3.91	0.5	4	11 NC 5/8"
324/6TSC	1.591	2.00	12.75	11	12.5	1.875	3.5	5.25	2.03	0.5	4	11 NC 5/8"
364/5TC	2.021	3.00	12.75	11	12.5	2.375	5.62	5.88	4.28	0.625	8	11 NC 5/8"
364/5TSC	1.591	3.00	12.75	11	12.5	1.875	3.5	5.88	2.03	0.5	8	11 NC 5/8"
404/5TC	2.450	3.00	13.5	11	12.5	2.875	7	6.625	5.65	0.75	8	11 NC 5/8"
404/5TSC	1.845	3.00	13.5	11	12.5	2.125	4	6.625	2.78	0.5	8	11 NC 5/8"
444/5TC	2.875	3.00	16.62	14	16	3.375	8.25	7.5	6.91	0.875	8	11 NC 5/8"
444/5TSC	2.021	3.00	16.62	14	16	2.375	4.5	7.5	3.03	0.625	8	11 NC 5/8"
447TC	2.875	3.00	16.62	14	16	3.375	8.25	7.5	6.91	0.875	8	11 NC 5/8"
447TSC	2.021	3.00	16.62	14	16	2.375	4.5	7.5	3.03	0.625	8	11 NC 5/8"
449TC	2.875	3.00	16.62	14	16	3.375	8.25	7.5	6.91	0.875	8	11 NC 5/8"
449TSC	2.021	3.00	16.62	14	16	2.375	4.5	7.5	3.03	0.62	8	11 NC 5/8"

\* Dimension "BA" de 143TC a 256TC difiere de dimensión NEMA

